96264879 <SATIN2 MWA L1230 48L35 32° 840 IO

IP67 | IK08 | 850°C | T_a25

A discreet linear floodlight for façade illumination applications. 48 LEDs driven at 350mA with 32° distribution. Electronic, fixed output control gear. Body: extruded aluminium (EN AW-6060 T6) painted textured silver grey. Sides: grey polycarbonate. Enclosure: UV stabilised polycarbonate. Stirrups: powder coated steel. Class II electrical, IP67, IK08. Surface mounted or recessed with optional ground recessed box. Pre-wired with 1m of 2x1mm² H05RNF cable (and 1m of DMX512 cable for DMX versions) at both ends. Complete with 4000K LED

Dimensions: 1232 x 75 x 70 mm
Luminaire input power: 46 W
Weight: 4.9 kg

TLG_SAT2_F_LEDS.jpg



TLG_SAT2_M_LD1.wmf

This product contains a light source of energy efficiency class E.

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting