FleXity

96627905 <FLEX 24L70-740 EWR CL1 CON T60 ANT

ISO 9223 C3		IP66	IK09								T_a -20 +25

FleXity

A modern, discreet and versatile post top LED lantern with a Extra Wide Road distribution. LED driver Programmable driving 24 LEDs at 700mA. Class I electrical, IP66, IK09. Canopy and base: die-cast aluminium (EN AC-46100) powder coated dark grey (close to RAL7043). Enclosure: clear polycarbonate. Complete with 4000K LED. Post top mounting to Ø60mm column, maximum spigot length 75mm. Pre-wired with 5m cable.

Surge protection: 10kV single pulse common mode and 8kV multipulse common mode and 6kV multipulse differential mode. If permanent DALI system is connected, 6kV multipulse common and differential mode.

Dimensions: 370 x 430 x 290 mm
Luminaire input power: 55 W
Luminaire luminous flux: 6513 lm
Luminaire efficacy: 118 lm/W
Weight: 4.5 kg
Scx: m²

TLG_FLEX_F_D60PDB.jpg

This product contains a light source of energy efficiency class D.

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting