96273576 <GAMMA 24L70-740 SC-S CL2 W5 T76 GY

IP66 | IK10 | T_a -20 +25

A modern, discreet and versatile post top LED lantern with a symmetric distribution. Electronic, fixed output control gear driving 24 LEDs at 700mA. Compatible with DALI, RF, Power Line, Minicell, Nema, Presence Detection. Class II electrical, IP66, IK10. Canopy and base: die-cast aluminium (EN AC-46100) powder coated grey (close to RAL9006). Enclosure: frosted polycarbonate. Complete with 4000K LED. Post top mounting to Ø76mm column, maximum spigot length 75mm. Pre-wired with 5m cable.

Dimensions: 430 x 370 x 396 mm
Luminaire input power: 53 W
Luminaire luminous flux: 5882 lm
Luminaire efficacy: 111 lm/W
Weight: 6.4 kg
Scx: 0.064 m²

TLG_GAML_F_D76PDB4000K.jpg

TLG_GAML_M_LD1.wmf

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting