THORN

96628217 <GAMMA 24L70-730 WS BP CL2 W5 T76 GY

IP66 IK10 Ta -20 +25

A modern, discreet and versatile post top LED lantern with a Wide Street distribution. Electronic, fixed output control gear driving 24 LEDs at 700mA. Compatible with DALI, RF, Power Line, Minicell, Nema, Presence Detection. Class II electrical, IP66, IK10. Canopy and base: die-cast aluminium (EN AC-46100) powder coated grey (close to RAL9006). Enclosure: frosted polycarbonate. Equipped with power reduction circuit, effective 3 hours before and 5 hours after a calculated midnight. Complete with 3000K LED. Post top mounting to Ø76mm column, maximum spigot length 75mm. Pre-wired with 5m cable.

Dimensions: 430 x 370 x 396 mm
Luminaire input power: 53 W
Luminaire luminous flux: 5207 lm
Luminaire efficacy: 98 lm/W
Weight: 6.4 kg
Scx: 0.064 m²

TLG_GAML_F_D76PDB3000K.jpg

TLG_GAML_M_LD1.wmf

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting