THORN

96628227 <GAMMA 24L35-730 WS BP CL1 W5 T60 GY

IP66 | IK10 | T_a -20 +35

A modern, discreet and versatile post top LED lantern with a Wide Street distribution. Electronic, fixed output control gear driving 24 LEDs at 350mA. Compatible with DALI, RF, Power Line, Minicell, Nema, Presence Detection. Class I electrical, IP66, IK10. Canopy and base: die-cast aluminium (EN AC-46100) powder coated grey (close to RAL9006). Enclosure: frosted polycarbonate. Equipped with power reduction circuit, effective 3 hours before and 5 hours after a calculated midnight. Complete with 3000K LED. Post top mounting to Ø60mm column, maximum spigot length 75mm. Pre-wired with 5m cable.

Dimensions: 430 x 370 x 396 mm
Luminaire input power: 28 W
Luminaire luminous flux: 2836 lm
Luminaire efficacy: 101 lm/W
Weight: 6.3 kg
Scx: 0.064 m²

TLG_GAML_F_D60PDB3000K.jpg

TLG_GAML_M_LD1.wmf

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting

THORN

96628227 <GAMMA 24L35-730 WS BP CL1 W5 T60 GY

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting