Alumet Control Direct

96274768 ALUMET CD 18L35-730 R/S PR SLA CL2 W4M

ISO 9223 C3 | IP66 | IK10 | T_a25

Alumet Control Direct

An architectural lighting column head with 18 LEDs driven at 350mA with a radially symmetric distribution and prismatic optic, configured for DALI control over additional wires, Top cap: die-cast aluminium. Diffuser: clear UV stabilised polycarbonate treated with anti graffiti varnish. Top cap and column: powder coated textured silver grey (close to RAL 9006), other RAL colours on request. Class II electrical, IK10, IP66. To be mounted on an Alumet column. With corridor function control (slave). Surge protection: 10kV single pulse common mode and 8kV multipulse common mode and 6kV multipulse differential mode. If permanent DALI system is connected, 6kV multipulse common and differential mode. Complete with 3000K LED

Dimensions: Ø200 x 1250 mm
Luminaire input power: 21 W
Luminaire luminous flux: 1553 lm
Luminaire efficacy: 74 lm/W
Weight: 9.9 kg
Scx: 0.079 m²

TLG_ALUM_F_DIR_LEDPR_LGY.jpg



TLG_ALUM_M_2LD1.wmf

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting