

Glacier II


Modern, decorative pendant in two sizes with a choice of light sources and direct or direct/indirect reflectors


- Easy installation
- Superior design, 2 sizes and 4 different reflectors to fit more applications
- · Ceiling rose in same design to complete the look
- LED options



Photographs, line drawings and photometric data are representative only. For specific product detail please select an individual product.







96548014

Material/Finish

Housing: die-cast zinc with satin grey finish

Reflector: prismatic polycarbonate, prismatic or opal glass and spun aluminium in textured grey

Suspension wire: steel

Protective lamp cover: frosted glass

Ceiling Rose: die-cast zinc with satin grey finish and white plastic

Installation/Mounting

Suspension: adjustable quick-lock 2.5m single wire suspension (supplied). Similar length of pre-installed braided flame retardant silicon cable (3 x 0,75mm²) (5 x 0,75mm² for dimmable versions) without plug for easy, neat installation Visible installation: mounts directly into the ceiling rose (ordered separately) 2 x 5 x 1,5mm² terminal block Concealed installation possible via pre-formed loop in suspension wire.

Housing neck features bayonet cap type mount for quick and easy reflector connection.

Repositional housing sleeve to facilitate maintenance of control gear.

HIT / HIT-CE versions supplied with safety glass cover.

Specification

To specify state:

Large/small decorative pendant with metal housing on single wire suspension for 12/20W LED, 18/26W TC-T, 18/26/42/57W TC-TEL, 20W HIT-TC-CE, 35/70/150W HIT-CE lamps. With prismatic/opal glass/prismatic polycarbonate/spun aluminium reflector and pre-installed 2.5m (3/5x0.75mm) flame retardant halogen free mains cable. As Thorn Glacier II.

ENEC, IP20, Gluehlampe, Beam_Suspended_W, HIT-CE_G12, Beam_Suspended_EEW, HIT-TC_CE_GU65, Beam_eControl_A, SC1, Beam_Emergency, CE, TC-T, TC-TEL, Ta=25, Ta=40°C, LED