

THORN

Oxane R-PEC (4000K)								
Lighting Distribution	Number of LEDs	Data	Oxane S			Oxane L		
			350mA	500mA	700mA	350mA	500mA	700mA
NR	12LEDs	Luminaire Flux (lm)	1323lm	1804lm	2409lm			
		Power consumption (W)	15W	21W	30W			
	24LEDs	Luminaire Flux (lm)	2587lm	3516lm	4669lm			
		Power consumption (W)	31W	42W	58W			
	36LEDs	Luminaire Flux (lm)	3908lm	5302lm	7012lm		5180lm	6830lm
		Power consumption (W)	42W	61W	85W		62W	85W
48LEDs	Luminaire Flux (lm)				4920lm	6720lm	8860lm	
	Power consumption (W)				55W	80W	111W	
WS	12LEDs	Luminaire Flux (lm)	1345lm	1835lm	2451lm			
		Power consumption (W)	15W	21W	30W			
	24LEDs	Luminaire Flux (lm)	2633lm	3578lm	4751lm			
		Power consumption (W)	31W	42W	58W			
	36LEDs	Luminaire Flux (lm)	3977lm	5395lm	7134lm		5031lm	6634lm
		Power consumption (W)	42W	61W	85W		62W	85W
48LEDs	Luminaire Flux (lm)				4780lm	6528lm	8602lm	
	Power consumption (W)				55W	80W	111W	
60LEDs	Luminaire Flux (lm)				6098lm	8322lm	10959lm	
	Power consumption (W)				67W	97W	137W	
72LEDs	Luminaire Flux (lm)				7955lm	10608lm	13654lm	
	Power consumption (W)				82W	115W	169W	

Luminous flux and connected load are subject to an initial tolerance of +/-10%

Data is subject to change due to continuous progress of LED characteristics. To check the effect on the luminaire, please contact us or visit our website