

# EyeKon LED

THORN

92900959 EYE CR LED1350-840 HFIX E3TX L BK

EN 55015	IP65	IK10	⊕	CE	⚡	EAC	⚡	⚡	850°C	T <sub>a</sub> 0 +25
-------------	------	------	---	----	---	-----	---	---	-------	-------------------------

## EyeKon LED

Round, impact resistant LED bulkhead luminaire.  
Electronic, DALI dimmable control gear with 3 hour,  
Self/DALI Addressable test, emergency lighting circuit.  
Class I electrical, IP65, IK10. Body: large size, die-cast  
aluminium (LM6), powder coated. Diffuser: opal  
polycarbonate with die-cast aluminium cross feature.  
Electrical connection via 6 x 2 x 2.5mm<sup>2</sup> terminal block.  
Complete with 4000K LED

Dimensions: Ø340 x 155 mm  
Luminaire input power: 16 W  
Weight: 3.9 kg



TLG\_EYKN\_F\_LGCRSBLKOP.jpg



TLG\_EYKN\_M\_LGE.wmf

This product contains a light source of energy efficiency class C.

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.  
© Thorn Lighting

**EyeKon LED**

**92900959 EYE CR LED1350-840 HFIX E3TX L BK**

**THORN**