

# Prisma

# THORN

## 96630828 PRISMA LED4400-840 HF FR L1200 TW

|          |      |   |      |   |    |   |     |   |   |   |       |
|----------|------|---|------|---|----|---|-----|---|---|---|-------|
| EN 55015 | IP44 | ▽ | IK06 | ⊕ | CE | Ⓢ | EAC | ☼ | Ⓢ | Ⓢ | 650°C |
|----------|------|---|------|---|----|---|-----|---|---|---|-------|

### Prisma

Slim Surface mounted LED luminaire. Electronic, fixed output control gear. Class I electrical, IP44. Body: pre-coated steel. End caps: white plastic. Diffuser: frosted acrylic. Keyhole fixing positions Ø14mm for direct mounting to ceiling, wall or brackets. Fixing centres: 1100mm. Two cable entries Ø19mm in the rear of the body and knockouts in the endcaps. Grommets included. Electrical connection via 3 x 2 x 2.5mm<sup>2</sup> piano key terminal block. Through Wiring. Complete with 4000K LED

Dimensions: 1216 x 166 x 64 mm  
Luminaire input power: 35.3 W  
Luminaire luminous flux: 4250 lm  
Luminaire efficacy: 120 lm/W  
Weight: 2.81 kg



TLG\_PRSM\_F\_01.jpg



TLG\_PRSM\_M\_LED\_LD1.wmf

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.  
© Thorn Lighting