

96633074 DUROLIGHT-C 4500-840 HF L1515

IP65	IK10					850°C		T _a -25 +45
------	------	--	--	--	--	-------	--	---------------------------


Durolight

Anti-vandal Surface mounted cornice LED luminaire.
 Electronic, fixed output control gear. IP65, IK10, Class I electrical. Body: 2mm sheet steel painted white (close to RAL9016). Gasket: non-ageing polyurethane foam.
 Diffuser: 3mm thick polycarbonate with outstanding impact resistance, connected and secured with tamper-resistant stainless steel twin hole screws to the body. Complete with 4000K LED

Dimensions: 1515 x 175 x 175 mm
 Luminaire input power: 46.7 W
 Luminaire luminous flux: 4497 lm
 Luminaire efficacy: 96 lm/W
 Weight: 13 kg



TLG_DURO_F_CORNER.jpg



TLG_DURO_M_LDC.wmf

This product contains a light source of energy efficiency class C.

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
 © Thorn Lighting

Durolight

96633074 DUROLIGHT-C 4500-840 HF L1515

THORN