

Beta 3

92936723 BETA 3 4100-840 HF E3 LRO Q625

IEC EN 60598-1 RG 0		IK03					650°C	T _a 0 +25
---------------------------	--	------	--	--	--	--	-------	-------------------------

Beta 3

A square ceiling recessed LED luminaire. Fixed output LED driver with 3 hour, manual test, emergency lighting circuit. Class I electrical, IP44_IP20, Impact strength: IK03. Body: sheet steel, white (close to RAL9016). Diffuser: Opalised PMMA with micro-prismatic foil inlay. Safety wire not included. Complete with 4000K LED.

UGR < 19 and L65 < 3000 cd/m² as per EN 12464

Dimensions: 622 x 622 x 34 mm
Luminaire input power: 33.6 W
Luminaire luminous flux: 4100 lm
Luminaire efficacy: 122 lm/W
Weight: 3.8 kg



TLG_BET3_F_MREQ.jpg



TLG_BET3_M_Q600.wmf

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Beta 3

92936723 BETA 3 4100-840 HF E3 LRO Q625

THORN