

IQ Beam

96636077 IQ BEAM HT 6300-840 MPT-F HFIX Q600

IEC EN 60598-1 RG 1		IP20	IK03					650 °C	T _a -20 +50
---------------------------	--	------	------	--	--	--	--	--------	---------------------------


IQ Beam

A linear optic, recessed modular LED luminaire for exposed T, plasterboard and concealed grid ceilings. DALI-2 dimmable, LED driver. Class I electrical, IP20, Impact strength: IK03. Body: white painted steel. Diffuser: micro prism structure acrylic with diffusing foil. Suitable for lay-in installation, pull up installation optional. Complete with 4000K LED.

Dimensions: 597 x 597 x 60 mm
 Luminaire input power: 50 W
 Luminaire luminous flux: 6300 lm
 Luminaire efficacy: 126 lm/W
 Weight: 4.26 kg



TLG_IQBM_F_HT_pers.jpg



TLG_IQBM_M_HT_P.wmf

This product contains a light source of energy efficiency class C.

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.