

## R2L2

96268439 R2L2 S 24L50 740 EWC CL1 GY

|                |      |      |   |    |   |     |   |   |                           |
|----------------|------|------|---|----|---|-----|---|---|---------------------------|
| ISO 9223<br>C5 | IP66 | IK08 | ⊕ | CE | ⚡ | EAC | 🔧 | 🔧 | T <sub>a</sub> -25<br>+50 |
|----------------|------|------|---|----|---|-----|---|---|---------------------------|

### R2L2

A small size LED road lighting lantern with 24 LEDs driven at 500mA with Extra Wide Street & Comfort optic. LED driver Programmable. Class I electrical, IP66, IK08. Housing: die-cast aluminium (EN AC-44300), powder coated textured light grey. Enclosure: tempered flat glass. Screws: stainless steel, Ecolubric® treated. Post top (Ø60/76mm, tilted 0°/5°/10°) or lateral (Ø34/42/49/60mm, tilted 0°/-5°/-10°/-15°) mounting. Complete with 4000K LED.

Dimensions: 655 x 362 x 155 mm  
 Luminaire input power: 38 W  
 Luminaire luminous flux: 5425 lm  
 Luminaire efficacy: 143 lm/W  
 Weight: 9.54 kg  
 Scx: 0.05 m<sup>2</sup>



TLG\_R2L2\_F\_SPDB.jpg



TLG\_R2L2\_M\_LDS.wmf

This product contains a light source of energy efficiency class D.

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.  
 © Thorn Lighting