

Omega Circular

96627770 OMEGA C LED2800-840 HF R400

THORN

| | | | | | | | | |
|------|------|---|---|---|---|---|---|-------------------------|
| IP20 | IK02 |  |  |  |  |  |  | T _a 0 +25 |
|------|------|---|---|---|---|---|---|-------------------------|


Omega Circular

A versatile, circular edge lit panel for recessed mounting in a Ø200mm cutout. Electronic, fixed output control gear. Class I electrical, IP20. Body: aluminium and steel, white (RAL 9016). Diffuser: acrylic opal. Complete with 4000K LED.

Dimensions: Ø400 x 55 mm
Luminaire input power: 33 W
Luminaire luminous flux: 2649 lm
Luminaire efficacy: 80 lm/W
Weight: 3.3 kg



TLG_OMGC_F_PDB.jpg



TLG_OMGC_M_2800.wmf

This product contains a light source of energy efficiency class E.

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting