

## R2L2

96272499 R2L2 S 12L35 740 WS CLO PM CL1 GY

ISO 9223 C5	IP66	IK08	⊕	CE	⚡	EAC	⚙️	⚙️	T <sub>a</sub> -25 +50
----------------	------	------	---	----	---	-----	----	----	---------------------------

### R2L2

A small size LED road lighting lantern with 12 LEDs driven at 350mA with Wide Street optic. LED driver Programmable. Class I electrical, IP66, IK08. Housing: die-cast aluminium (EN AC-44300), powder coated textured light grey. Enclosure: tempered flat glass. Screws: stainless steel, Ecolubric® treated. Post top (Ø60/76mm, tilted 0°/5°/10°) or lateral (Ø34/42/49/60mm, tilted 0°/-5°/-10°/-15°) mounting. Driver programmed for Constant Light Output operation with fitted with Mini Photocell. Complete with 4000K LED.

Dimensions: 655 x 362 x 155 mm  
 Luminaire input power: 15 W  
 Luminaire luminous flux: 2036 lm  
 Luminaire efficacy: 136 lm/W  
 Weight: 9.16 kg  
 Scx: 0.05 m<sup>2</sup>



TLG\_R2L2\_F\_SPDB.jpg



TLG\_R2L2\_M\_LDS.wmf

This product contains a light source of energy efficiency class D.

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

**R2L2**

**96272499 R2L2 S 12L35 740 WS CLO PM CL1 GY**

**THORN**