

96643930 TR 72L50-730 NR BP CL1 OP W9 L60E

| | | | | | | | | | | |
|----------------|------|------|--|--|--|--|--|--|-------------------------|--|
| ISO 9223 C5 | IP66 | IK08 | | | | | | | T _a 0 +25 | |
|----------------|------|------|--|--|--|--|--|--|-------------------------|--|

Thor

A large size, smart urban LED lantern with 72 LEDs driven at 500mA with Narrow Road optic and UV stabilised polycarbonate dome with opal finish. Class I electrical, IP66, IK08. Body, bracket and ring: die-cast aluminium (AS12U, LM6 equivalent, EN AC-44300) treated against corrosion, powder coated anthracite (close to RAL7043). Enclosure: 4mm toughened flat glass. Screws and closing set: stainless steel. Pre-wired with 9m cable. Side entry mounting to Ø60mm spigot, tilt 0°, adjustable from -15° to +10°. Equipped with power reduction circuit, effective 3 hours before and 5 hours after a calculated midnight. Complete with 3000K LED.

Dimensions: Ø577 x 155 mm
 Luminaire input power: 115 W
 Luminaire luminous flux: 14412 lm
 Luminaire efficacy: 125 lm/W
 Weight: 14.6 kg
 Scx: 0.044 m²



TLG_THRL_F_MLEOP0.jpg



TLG_THOR_M_BRK.wmf

This product contains light sources of energy efficiency class D.

Thor

96643930 TR 72L50-730 NR BP CL1 OP W9 L60E

THORN