

96643963 TR 72L50-740 SC BP CL2 FD W9 L60E

| | | | | | | | | | |
|----------------|------|------|--|--|--|--|--|-------------------------|--|
| ISO 9223 C5 | IP66 | IK08 | | | | | | T _a 0 +25 | |
|----------------|------|------|--|--|--|--|--|-------------------------|--|

Thor

A large size, smart urban LED lantern with 72 LEDs driven at 500mA with Street & Comfort optic and UV stabilised polycarbonate dome with anthracite finish (close to RAL7043). Class II electrical, IP66, IK08. Body, bracket and ring: die-cast aluminium (AS12U, LM6 equivalent, EN AC-44300) treated against corrosion, powder coated anthracite (close to RAL7043). Enclosure: 4mm toughened flat glass. Screws and closing set: stainless steel. Pre-wired with 9m cable. Side entry mounting to Ø60mm spigot, tilt 0°, adjustable from -15° to +10°. Equipped with power reduction circuit, effective 3 hours before and 5 hours after a calculated midnight. Complete with 4000K LED.

Dimensions: Ø577 x 155 mm
 Luminaire input power: 109 W
 Luminaire luminous flux: 15720 lm
 Luminaire efficacy: 144 lm/W
 Weight: 14.8 kg
 Scx: 0.044 m²



TLG_THRL_F_MLEFD0.jpg



TLG_THOR_M_BRK.wmf

This product contains light sources of energy efficiency class E.