

96665454 CQ 36L50 740 SC BS 3550 CL1 M42 GY-S

| | | | | | | | | | | | | |
|----|----------------|----------------|------|------|---|----|-----|---|---|---|-------------------|--|
| CB | ISO 9223 C5 | PLUG * 11 * | IP66 | IK08 | ⏏ | CE | EAC | ⚡ | ⊗ | ⊗ | T _a 25 | |
|----|----------------|----------------|------|------|---|----|-----|---|---|---|-------------------|--|

CiviTEQ

A small size LED road lighting lantern with 36 LEDs driven at 500mA with Street & Comfort optic. Electronic, fixed output control gear. Class I electrical, IP66, IK08. Housing: die-cast aluminium (EN AC-44300), Light grey 150 sanded textured (close to RAL9006). Enclosure: toughened flat glass. Screws: stainless steel, Ecolubric® treated. Supplied with Ø42mm spigot adaptor which can be fitted for post-top (0°/5°/10° tilt) or side-entry (-20°/-15°/-10°/-5°/0° tilt). Equipped with 50% power reduction circuit, effective 3 hours before and 5 hours after a calculated midnight. It can be deactivated at installation with an easily accessible internal switch. Complete with 3000K LED. Surge protection: 10kV single pulse common mode and 8kV multipulse common mode and 6kV multipulse differential mode. If permanent DALI system is connected, 6kV multipulse common and differential mode.

Dimensions: 390 x 230 x 133 mm
 Luminaire input power: 55 W
 Luminaire luminous flux: 8674 lm
 Luminaire efficacy: 158 lm/W
 Weight: 5.5 kg
 Scx: 0.077 m²



TLG_CTEQ_F_SMTP36LEDPDB.jpg



TLG_CETQ_M_S.wmf

This product contains light sources of energy efficiency class E.