

96665489 CQ 72L35 740 WS BS 3550 CL1 M42 GY-S

|    |                |                |      |      |   |    |     |   |   |                   |  |
|----|----------------|----------------|------|------|---|----|-----|---|---|-------------------|--|
| CB | ISO 9223<br>C5 | PLUG<br>* 11 * | IP66 | IK08 | ⏏ | CE | EAC | ⚡ | ☀ | T <sub>a</sub> 25 |  |
|----|----------------|----------------|------|------|---|----|-----|---|---|-------------------|--|

## CiviTEQ

A large size LED road lighting lantern with 72 LEDs driven at 350mA with Wide Street optic. Electronic, fixed output control gear. Class I electrical, IP66, IK08. Housing: die-cast aluminium (EN AC-44300), Light grey 150 sanded textured (close to RAL9006). Enclosure: toughened flat glass. Screws: stainless steel, Ecolubric® treated. Supplied with Ø42mm spigot adaptor which can be fitted for post-top (0°/5°/10° tilt) or side-entry (-20°/-15°/-10°/-5°/0° tilt). Equipped with 50% power reduction circuit, effective 3 hours before and 5 hours after a calculated midnight. It can be deactivated at installation with an easily accessible internal switch. Complete with 4000K LED. Surge protection: 10kV single pulse common mode and 8kV multipulse common mode and 6kV multipulse differential mode. If permanent DALI system is connected, 6kV multipulse common and differential mode.

Dimensions: 580 x 230 x 160 mm  
 Luminaire input power: 75 W  
 Luminaire luminous flux: 12438 lm  
 Luminaire efficacy: 166 lm/W  
 Weight: 9.2 kg  
 Scx: 0.115 m²



TLG\_CTEQ\_F\_LMTP72LEDPDB.jpg



TLG\_CETQ\_M\_L.wmf

This product contains light sources of energy efficiency class E.