

96665502 CQ 48L50 740 WSC BS 3550 CL1 M42 GY-S

| | | | | | | | | | | | |
|----|----------------|----------------|------|------|---|----|-----|---|---|-------------------|--|
| CB | ISO 9223 C5 | PLUG * 11 * | IP66 | IK08 | ⊕ | CE | EAC | ⚡ | ☀ | T _a 25 | |
|----|----------------|----------------|------|------|---|----|-----|---|---|-------------------|--|

CiviTEQ

A large size LED road lighting lantern with 48 LEDs driven at 500mA with Wide Street & Comfort optic. Electronic, fixed output control gear. Class I electrical, IP66, IK08. Housing: die-cast aluminium (EN AC-44300), Light grey 150 sanded textured (close to RAL9006). Enclosure: toughened flat glass. Screws: stainless steel, Ecolubric® treated. Supplied with Ø42mm spigot adaptor which can be fitted for post-top (0°/5°/10° tilt) or side-entry (-20°/-15°/-10°/-5°/0° tilt). Equipped with 50% power reduction circuit, effective 3 hours before and 5 hours after a calculated midnight. It can be deactivated at installation with an easily accessible internal switch. Complete with 4000K LED. Surge protection: 10kV single pulse common mode and 8kV multipulse common mode and 6kV multipulse differential mode. If permanent DALI system is connected, 6kV multipulse common and differential mode.

Dimensions: 580 x 230 x 160 mm
 Luminaire input power: 71.1 W
 Luminaire luminous flux: 11440 lm
 Luminaire efficacy: 161 lm/W
 Weight: 8.4 kg
 Scx: 0.115 m²



TLG_CTEQ_F_LMTP72LEDPDB.jpg



TLG_CETQ_M_L.wmf

This product contains light sources of energy efficiency class D.

CiviTEQ

96665502 CQ 48L50 740 WSC BS 3550 CL1 M42 GY-S

THORN