

## 92900296 IQ WAVE LED3100-840 HFIX E3TX Q622 MRE

↓ IP20 ↑ IP44	IK03	⊕	CE	⚡	⚙️	⚙️	650°C	T <sub>a</sub> 0 +25	
------------------	------	---	----	---	----	----	-------	-------------------------	--


### IQ Wave

Recessed modular, direct LED luminaire. Electronic, DALI dimmable control gear with 3 hour, Self/DALI Addressable test, emergency lighting circuit. Class I electrical, IP44\_IP20, IK03. Body: highly reflective steel. Frame and end caps: polycarbonate. Diffuser: polycarbonate with aluminium heatsink. Gear tray: powder coated white steel. Suitable for lay in or pull up (with accessory) installation. Complete with 4000K LED

Dimensions: 622 x 622 x 97 mm  
Luminaire input power: 30 W  
Luminaire luminous flux: 3200 lm  
Luminaire efficacy: 107 lm/W  
Weight: 5.1 kg



TLG\_IQWV\_F\_PDB.jpg



TLG\_IQWV\_M\_625.wmf

This product contains a light source of energy efficiency class D.

**IQ Wave**

**92900296 IQ WAVE LED3100-840 HFIX E3TX Q622 MRE**

**THORN**