

96628998 CQ 72L70 730 NR BS 3550 CL2 M60 ANT

| | | | | | | | | | | |
|----|----------------|----------------|------|------|--|----|-----|--|------|--|
| CB | ISO 9223 C5 | PLUG * 11 * | IP66 | IK08 | | CE | EAC | | Ta25 | |
|----|----------------|----------------|------|------|--|----|-----|--|------|--|


CiviTEQ

A large size LED road lighting lantern with 72 LEDs driven at 700mA with Narrow Road optic. Electronic, fixed output control gear. Class II electrical, IP66, IK08. Housing: die-cast aluminium (EN AC-44300), powder coated anthracite (close to RAL7043). Enclosure: toughened flat glass. White framed with etched border. Screws: stainless steel, Ecolubric® treated. Supplied with Ø60mm spigot adaptor which can be fitted for post-top (0°/5°/10° tilt) or side-entry (-20°/-15°/-10°/-5°/0° tilt). Complete with 3000K LED. Surge protection: 10kV single pulse common mode and 8kV multipulse common mode and 6kV multipulse differential mode. If permanent DALI system is connected, 6kV multipulse common and differential mode.

Dimensions: 580 x 230 x 160 mm
 Luminaire input power: 149 W
 Luminaire luminous flux: 20642 lm
 Luminaire efficacy: 139 lm/W
 Weight: 9.2 kg
 Scx: 0.115 m²



TLG_CTEQ_F_LMTP60ANTPDB.jpg



TLG_CETQ_M_L.wmf

This product contains light sources of energy efficiency class D.

CiviTEQ

96628998 CQ 72L70 730 NR BS 3550 CL2 M60 ANT

THORN