







EyeKon LED

92900528 EYE BE LED1550-840 HFIX L SIL

THORN

EN 55015	IP65	IK10							850°C	T _a -20 +35
-------------	------	------	---	---	---	---	---	---	-------	---------------------------

EyeKon LED

Round, impact resistant LED bulkhead luminaire.
Electronic, DALI dimmable control gear. Class I electrical,
IP65, IK10. Body: large size, die-cast aluminium (LM6),
powder coated silver grey. Diffuser: opal polycarbonate
with die-cast aluminium bezel feature. Electrical connection
via 5 x 2 x 2.5mm² terminal block. Complete with 4000K
LED

Dimensions: Ø340 x 155 mm

Luminaire input power: 16 W

Weight: 3.47 kg



TLG_EYKN_F_LGBEZANTHOP.jpg



TLG_EYKN_M_LGE.wmf

This product contains a light source of energy efficiency class C.

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting

EyeKon LED

92900528 EYE BE LED1550-840 HFIX L SIL

THORN