







# EyeKon LED

92900826 EYE VS LED700-840 HF E3TX S BK

THORN

EN 55015	IP65	IK10							850°C	T <sub>a</sub> 0 +25	
-------------	------	------	---	---	---	---	---	---	-------	-------------------------	--


## EyeKon LED

Round, impact resistant LED bulkhead luminaire.  
Electronic, fixed output control gear with 3 hour, Self/DALI  
Addressable test, emergency lighting circuit. Class I  
electrical, IP65, IK10. Body: small size, die-cast aluminium  
(LM6), powder coated. Diffuser: opal polycarbonate with  
die-cast aluminium visor feature. Electrical connection via 6  
x 2 x 2.5mm<sup>2</sup> terminal block. Complete with 4000K LED

Dimensions: Ø285 x 150 mm

Luminaire input power: 11 W

Weight: 3.2 kg



TLG\_EYKN\_F\_SMVSANTHOP.jpg



TLG\_EYKN\_M\_SML.wmf

This product contains a light source of energy efficiency class C.

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.  
© Thorn Lighting

**EyeKon LED**

**92900826 EYE VS LED700-840 HF E3TX S BK**

**THORN**