







EyeKon LED

THORN

92900844 EYE BE LED700-840 HF E3TX S ANT

EN 55015	IP65	IK10							850°C	T _a 0 +25	
-------------	------	------	---	---	---	---	---	---	-------	-------------------------	--

EyeKon LED

Round, impact resistant LED bulkhead luminaire.
Electronic, fixed output control gear with 3 hour, Self/DALI
Addressable test, emergency lighting circuit. Class I
electrical, IP65, IK10. Body: small size, die-cast aluminium
(LM6), powder coated anthracite. Diffuser: opal
polycarbonate with die-cast aluminium bezel feature.
Electrical connection via 6 x 2 x 2.5mm² terminal block.
Complete with 4000K LED


Dimensions: Ø285 x 150 mm

Luminaire input power: 7 W

Weight: 2.4 kg



TLG_EYKN_F_SMBEZANTHOP.jpg



TLG_EYKN_M_SML.wmf

This product contains a light source of energy efficiency class C.

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting

EyeKon LED

92900844 EYE BE LED700-840 HF E3TX S ANT

THORN