

## Piazza II LED

96666263 PIAZZA II LED 2700-840 HF E3TX ANT

IP65	IK10							T <sub>a</sub> 0 +25
------	------	--	--	--	--	--	--	-------------------------

### Piazza II LED

A robust Wall mounted luminaire. Electronic, fixed output control gear with 3 hour, Self/DALI Addressable test, emergency lighting circuit. Back plate: die-cast aluminium, painted anthracite. Body: anthracite polycarbonate. Ø20mm cable entry via rear or side conduit entries, BESA compatible. IP65, IK10. Complete with 4000K LED.

Dimensions: 381 x 196 x 305 mm  
 Luminaire input power: 25 W  
 Luminaire luminous flux: 2910 lm  
 Luminaire efficacy: 116 lm/W  
 Weight: 3.1 kg



TLG\_PIA2\_F\_PDB.jpg



TLG\_PIA2\_M\_LD1.wmf

This product contains a light source of energy efficiency class E.

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.