

# IQ Wave SP

# THORN

96629299 IQ SUSP S LED6700-840 HFIX E3TX ML6

IP20	IK05						650°C	T <sub>a</sub> 0 +25
------	------	--	--	--	--	--	-------	-------------------------


## IQ Wave SP

A lightweight, Suspended, LED luminaire with MV Tech optic. Electronic, DALI dimmable control gear with 3 hour, Self/DALI Addressable test, emergency lighting circuit. Class I electrical, IP20, IK05. Body, diffuser, frame and endcaps: polycarbonate finished in white (close to RAL9016). Gear tray: pre-coated white steel. Fitted with 6 core cable of 2,5m length. Suspension wires included. Ceiling rose to be ordered separately. Complete with 4000K LED

Dimensions: 1140 x 210 x 70 mm  
Luminaire input power: 61 W  
Luminaire luminous flux: 6700 lm  
Luminaire efficacy: 110 lm/W  
weight: 5.1 kg



TLG\_IQSU\_F\_SUS\_PDB.jpg



TLG\_IQSU\_M\_SUS.wmf

This product contains a light source of energy efficiency class D.

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at  $\pm 10\%$ . Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.  
© Thorn Lighting

# **IQ Wave SP**

**96629299 IQ SUSP S LED6700-840 HFIX E3TX ML6**

**THORN**