

# EyeKon LED

THORN

92900886 EYE VS LED1000-840 HF E3 L BK

EN 55015	IP65	IK10						850°C	T <sub>a</sub> 0 +25	
-------------	------	------	--	--	--	--	--	-------	-------------------------	--


## EyeKon LED

Round, impact resistant LED bulkhead luminaire.  
Electronic, fixed output control gear with 3 hour, manual  
test, emergency lighting circuit. Class I electrical, IP65,  
IK10. Body: large size, die-cast aluminium (LM6), powder  
coated. Diffuser: opal polycarbonate with die-cast  
aluminium feature. Electrical connection via 4 x 2 x 2.5mm<sup>2</sup>  
terminal block. Complete with 4000K LED


Dimensions: Ø340 x 155 mm

Luminaire input power: 16 W

Weight: 3.6 kg



TLG\_EYKN\_F\_LGVSANTHOP.jpg



TLG\_EYKN\_M\_LGE.wmf

This product contains a light source of energy efficiency class C.

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.  
© Thorn Lighting

**EyeKon LED**

**92900886 EYE VS LED1000-840 HF E3 L BK**

**THORN**