

## 96630835 PRISMA LED6200-830 HF FR L1200 TW

EN 55015	IP44	▽	IK06	⊕	CE	⚡	EAC	☀️	⚙️	650°C	
-------------	------	---	------	---	----	---	-----	----	----	-------	--


### Prisma

Slim Surface mounted LED luminaire. Electronic, fixed output control gear. Class I electrical, IP44. Body: pre-coated steel. End caps: white plastic. Diffuser: frosted acrylic. Keyhole fixing positions Ø14mm for direct mounting to ceiling, wall or brackets. Fixing centres: 1100mm. Two cable entries Ø19mm in the rear of the body and knockouts in the endcaps. Grommets included. Electrical connection via 3 x 2 x 2.5mm<sup>2</sup> piano key terminal block. Through Wiring. Complete with 3000K LED

Dimensions: 1216 x 166 x 64 mm  
 Luminaire input power: 53.5 W  
 Luminaire luminous flux: 5700 lm  
 Luminaire efficacy: 107 lm/W  
 Weight: 2.81 kg



TLG\_PRSM\_F\_01.jpg



TLG\_PRSM\_M\_LED\_LD1.wmf

**Prisma**

**96630835 PRISMA LED6200-830 HF FR L1200 TW**

**THORN**