

# R2L2

# THORN

96630720 R2L2 M 96L90-740 NR BS 3550 CL1 GY

|                |      |      |   |    |   |     |   |   |      |
|----------------|------|------|---|----|---|-----|---|---|------|
| ISO 9223<br>C5 | IP66 | IK08 | ⊕ | CE | ⚡ | EAC | 🔧 | 🔧 | Ta25 |
|----------------|------|------|---|----|---|-----|---|---|------|

## R2L2

A medium size LED road lighting lantern with 96 LEDs driven at 900mA with Narrow Road optic. LED driver Programmable. Class I electrical, IP66, IK08. Housing: die-cast aluminium, powder coated textured light grey. Enclosure: tempered flat glass. Screws: stainless steel, Ecolubric® treated. Post top (Ø60/76mm, tilted 0°/5°/10°) or lateral (Ø34/42/49/60mm, tilted 0°/-5°/-10°/-15°) mounting. Equipped with 50% power reduction circuit, effective 3 hours before and 5 hours after a calculated midnight. It can be deactivated at installation with an easily accessible internal switch. Complete with 4000K LED.

Dimensions: 880 x 370 x 155 mm  
Luminaire input power: 257.8 W  
Luminaire luminous flux: 37798 lm  
Luminaire efficacy: 147 lm/W  
Weight: 13.64 kg  
Scx: 0.06 m<sup>2</sup>



TLG\_R2L2\_F\_MPDB.jpg



TLG\_R2L2\_M\_LDM.wmf

This product contains light sources of energy efficiency classes D, E.

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.  
© Thorn Lighting