

# PopPack

# THORN

## 96631542 POPPACK LED 4500-840 HF L1200

IP20	IK03							650°C	T <sub>a</sub> -20 +25
------	------	--	--	--	--	--	--	-------	---------------------------

### PopPack

Batten LED luminaire. Electronic, fixed output control gear.  
Body: coated, formed steel, white (RAL9016). End caps:  
injection moulded polycarbonate,. Diffuser: textured opal  
acrylic. Electrical connection via 3 x 2 x 2.5mm<sup>2</sup> terminal  
block. Complete with 4000K LED

Dimensions: 1168 x 60 x 74 mm  
Luminaire input power: 35.6 W  
Luminaire luminous flux: 4650 lm  
Luminaire efficacy: 131 lm/W  
Weight: 1.4 kg



TLG\_POPL\_F\_PDB\_EMPTY.jpg



TLG\_POPL\_M\_LD1.wmf

This product contains a light source of energy efficiency class D.

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at  $\pm 10\%$ . Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.  
© Thorn Lighting