

## PopPack

96631555 POPPACK LED 5000-840 HF E3 L1500

IP20	IK03							650°C	T <sub>a</sub> 0 +25
------	------	--	--	--	--	--	--	-------	-------------------------

### PopPack

Batten LED luminaire. Electronic, fixed output control gear with 3 hour, manual test, emergency lighting circuit. Body: coated, formed steel, white (RAL9016). End caps: injection moulded polycarbonate, white. Diffuser: textured opal acrylic. Electrical connection via (3 + 3) x 2 x 2.5mm<sup>2</sup> terminal block. Complete with 4000K LED

Dimensions: 1449 x 60 x 74 mm  
 Luminaire input power: 36 W  
 Luminaire luminous flux: 4900 lm  
 Luminaire efficacy: 136 lm/W  
 Weight: 2.3 kg



TLG\_POPL\_F\_PDB\_EMPTY.jpg



TLG\_POPL\_M\_LD1.wmf

This product contains light sources of energy efficiency class D.

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.  
 © Thorn Lighting

**PopPack**

**96631555 POPPACK LED 5000-840 HF E3 L1500**

**THORN**