

IQ Wave SP

92903992 IQ SUSP S LED4250-840 BC E3 ML4

THORN

IP20	IK05						650°C	T _a 0 +25	
------	------	---	---	---	---	---	-------	-------------------------	--

IQ Wave SP

A lightweight, Suspended, LED luminaire with MV Tech optic. Electronic, dimmable control gear, Wireless connection via app with Bluetooth® 4.x - basicDIM Wireless Local battery luminaire, manual test (3 hours). Class I electrical, IP20, IK05. Body, diffuser, frame and endcaps: polycarbonate finished in white (close to RAL9016). Gear tray: pre-coated white steel. Fitted with 4 core cable of 2, 5m length. Complete with 4000K LED

Radio definition: basicDIM Wireless - Bluetooth® 4.x,
Radio frequency: 2.4...2.483 GHz, Radio power: +4 dBm.

Dimensions: 1140 x 210 x 70 mm
Luminaire input power: 35 W
Luminaire luminous flux: 4250 lm
Luminaire efficacy: 121 lm/W
weight: 5.2 kg



TLG_IQSU_F_SUS_PDB.jpg



TLG_IQSU_M_SUS.wmf

This product contains a light source of energy efficiency class C.

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at $\pm 10\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting

IQ Wave SP

92903992 IQ SUSP S LED4250-840 BC E3 ML4

THORN