

# Omega Pro 2

92915932 OP2 4400-840 MPT HFIX Q625

THORN

|    |                           |  |  |               |      |  |    |  |  |       |                         |  |
|----|---------------------------|--|--|---------------|------|--|----|--|--|-------|-------------------------|--|
| CB | IEC EN<br>60598-1<br>RG 0 |  |  | IP20<br>↑IP40 | IK03 |  | CE |  |  | 650°C | T <sub>a</sub> 0<br>+35 |  |
|----|---------------------------|--|--|---------------|------|--|----|--|--|-------|-------------------------|--|

## Omega Pro 2

A recessed/surface/suspended, edge-lit LED luminaire.  
LED driver, DALI-2 dimmable. Class II electrical,  
IP40\_IP20, Impact strength: IK03. Body: sheet steel,  
finished white (close to RAL9016). Diffuser: UV-stabilised  
polycarbonate microprismatic optic for maximised spacing.  
Electrical connection via piano key terminals, loop-in/loop-  
out possible. Complete with 4000K LED, Colour Rendering  
Index min.: 80

Dimensions: 622 x 622 x 55 mm  
Luminaire input power: 35 W  
Luminaire luminous flux: 4450 lm  
Luminaire efficacy: 127 lm/W  
Weight: 5.45 kg



TLG\_OMP2\_F\_QMPT\_PDB.jpg



TLG\_OMP2\_M\_Q.wmf

This product contains a light source of energy efficiency class D.

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at  $\pm 10\%$ . Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.  
© Thorn Lighting

## **Omega Pro 2**

**92915932 OP2 4400-840 MPT HFIX Q625**

THORN