

Omega Pro 2

92916319 OP2 3800-840 MPT HFIX E3D 3X12

THORN

| | | | | | | | | | | | | | | | | | | | | |
|----|---------------------------|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|-------|-------------------------|
| CB | IEC EN 60598-1 RG 0 | | | | | | | | | | | | | | | | | | 650°C | T _a 0 +35 |
|----|---------------------------|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|-------|-------------------------|

Omega Pro 2

A recessed/surface/suspended, edge-lit LED luminaire. LED driver, DALI-2 dimmable with 3 hour, Self/DALI Addressable test, emergency lighting circuit. Class II electrical, IP40_IP20, Impact strength: IK03. Body: sheet steel, finished white (close to RAL9016). Diffuser: UV-stabilised polycarbonate microprismatic optic for maximised spacing. Electrical connection via piano key terminals, loop-in/loop-out possible. Complete with 4000K LED, Colour Rendering Index min.: 80

Dimensions: 1197 x 297 x 57 mm
Luminaire input power: 29.1 W
Luminaire luminous flux: 3800 lm
Luminaire efficacy: 131 lm/W
Weight: 5.8 kg



TLG_OMP2_F_RMPT_PDB.jpg



TLG_OMP2_M_L.wmf

This product contains a light source of energy efficiency class D.

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at $\pm 10\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting

Omega Pro 2

92916319 OP2 3800-840 MPT HFIX E3D 3X12

THORN