

Omega Pro 2

92916335 OP2 3000-840 OP HF E3 3X12

THORN

IEC EN 60598-1 RG 0			IK03				650°C
---------------------------	---	---	------	---	---	---	-------


Omega Pro 2

A recessed/surface/suspended, edge-lit LED luminaire.
LED driver, with 3 hour, manual test, emergency lighting circuit. Class II electrical, IP44_IP20, Impact strength: IK03.
Body: sheet steel, finished white (close to RAL9016).
Diffuser: UV-stabilised polycarbonate opal optic for wide light distribution. Electrical connection via piano key terminals, loop-in/loop-out possible. Complete with 4000K LED, Colour Rendering Index min.: 80

Dimensions: 1197 x 297 x 57 mm
Luminaire input power: 24.4 W
Luminaire luminous flux: 2850 lm
Luminaire efficacy: 117 lm/W
Weight: 5.79 kg



TLG_OMP2_F_RH_PDB.jpg



TLG_OMP2_M_L.wmf

This product contains a light source of energy efficiency class D.

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at $\pm 10\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting