


Omega Pro 2

92916339 OP2 3000-840 OP HFIX 3X12

THORN



Omega Pro 2

A recessed/surface/suspended, edge-lit LED luminaire.
LED driver, DALI-2 dimmable. Class II electrical,
IP44_IP20, Impact strength: IK03. Body: sheet steel,
finished white (close to RAL9016). Diffuser: UV-stabilised
polycarbonate opal optic for wide light distribution.
Electrical connection via piano key terminals, loop-in/loop-
out possible. Complete with 4000K LED, Colour Rendering
Index min.: 80

Dimensions: 1197 x 297 x 57 mm
Luminaire input power: 23.7 W
Luminaire luminous flux: 2850 lm
Luminaire efficacy: 120 lm/W
Weight: 5.28 kg



TLG_OMP2_F_RH_PDB.jpg



TLG_OMP2_M_L.wmf

This product contains a light source of energy efficiency class D.

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at $\pm 10\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting