

# Omega Pro 2

92916346 OP2 4400-840 OP HF E3 3X12

THORN

IEC EN 60598-1 RG 0			IK03				650 °C
---------------------------	---	---	------	---	---	---	--------

## Omega Pro 2

A recessed/surface/suspended, edge-lit LED luminaire.  
LED driver, with 3 hour, manual test, emergency lighting circuit. Class II electrical, IP44\_IP20, Impact strength: IK03.  
Body: sheet steel, finished white (close to RAL9016).  
Diffuser: UV-stabilised polymethylmethacrylate opal optic for wide light distribution. Electrical connection via piano key terminals, loop-in/loop-out possible. Complete with 4000K LED, Colour Rendering Index min.: 80

Dimensions: 1197 x 297 x 57 mm  
Luminaire input power: 36 W  
Luminaire luminous flux: 4250 lm  
Luminaire efficacy: 118 lm/W  
Weight: 5.79 kg



TLG\_OMP2\_F\_RH\_PDB.jpg



TLG\_OMP2\_M\_L.wmf

This product contains a light source of energy efficiency class D.

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at  $\pm 10\%$ . Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.  
© Thorn Lighting

## Omega Pro 2

92916346 OP2 4400-840 OP HF E3 3X12

THORN