






Contrast

THORN

96633441 CONT3 4L50-822-40 WB NG IO ANT

| | | | | | | | | |
|----------------|---|------|------|---|---|---|---|---------------------------|
| ISO 9223 C5 |  | IP66 | IK08 |  |  |  |  | T _a -20 +35 |
|----------------|---|------|------|---|---|---|---|---------------------------|

Contrast


A small architectural Bracket mounted LED floodlight with 4 LEDs driven at 500mA and a wide beam distribution. ,. Pre-wired with IP66 connector, gear box to be ordered separately. Class II electrical, IP66, IK08. Body: die-cast, powder coated, textured anthracite (close to RAL7043). Compatible with coastal environments. Glass: tempered, 5mm thick. Gasket: EPDM. Screws: geomet. Complete with 2200-4000K balanced white LEDs

,

Dimensions: Ø83 x 103 mm
Luminaire input power: 7 W
Luminaire luminous flux: 293 lm
Luminaire efficacy: 42 lm/W
Weight: 1.03 kg



TLG_CON3_F_XS.jpg



TLG_CONL_M_4L.wmf

This product contains a light source of energy efficiency class F.

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at $\pm 10\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting

Contrast

96633441 CONT3 4L50-822-40 WB NG IO ANT

THORN