

# Omega Pro 2

92920664 OP2 3800-927-65 CKIT MPT 3X12D

THORN

CB	IEC EN 60598-1 RG 0			IP20 ↑ IP40	IK03		CE			650°C	T <sub>a</sub> 0 +35	
----	---------------------------	--	--	----------------	------	--	----	--	--	-------	-------------------------	--

## Omega Pro 2

A recessed/surface/suspended, edge-lit LED luminaire.  
LED driver, DALI-2 dimmable. Class II electrical,  
IP40\_IP20, Impact strength: IK03. Body: sheet steel,  
finished white (close to RAL9016). Diffuser: UV-stabilised  
polycarbonate microprismatic optic for maximised spacing.  
Electrical connection via 7 pole piano key terminals, loop-  
in/loop-out possible. Complete with VCT technology  
(variable colour temperature), stepless tunable from 2700-  
6500K, DT8., Colour Rendering Index min.: 90

Dimensions: 1247 x 309 x 57 mm  
Luminaire input power: 39.8 W  
Luminaire luminous flux: 3800 lm  
Luminaire efficacy: 95 lm/W  
Weight: 6.05 kg



TLG\_OMP2\_F\_RMPT\_PDB.jpg



TLG\_OMP2\_M\_L.wmf

This product contains a light source of energy efficiency class D.

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.  
© Thorn Lighting