

## 96634309 CT L 60L70-730 NR CL2 T60F ANT

|                |  |  |      |      |  |  |  |  |  |  |                   |  |
|----------------|--|--|------|------|--|--|--|--|--|--|-------------------|--|
| ISO 9223<br>C5 |  |  | IP66 | IK08 |  |  |  |  |  |  | T <sub>a</sub> 35 |  |
|----------------|--|--|------|------|--|--|--|--|--|--|-------------------|--|

### Carat


An elegant urban lantern with durable performance. Programmable LED driver, set for fixed output, driving 60 LEDs at 700mA. Body: large size, die-cast aluminium (EN AC-44300), anthracite (close to RAL7043). Shaft: anthracite (close to RAL7043). Cover: glass. Fixings: stainless steel with anti-galvanic treatment. Narrow Road optic, with Colour Rendering Index min.: 70 Correlated colour temperature\*: 3000 Kelvin LEDs supplied. Class II electrical, Impact strength: IK08, IP66, T<sub>a</sub> max.: 35°C. Supplied with Ø60mm spigot adaptor pre-fitted for post-top, 5° tilt.

Surge protection: 10kV single pulse common mode and 8kV multipulse common mode and 6kV multipulse differential mode. If permanent DALI system is connected, 6kV multipulse common and differential mode.

Dimensions: Ø510 x 87 mm  
Luminaire input power: 126 W  
Luminaire luminous flux: 17255 lm  
Luminaire efficacy: 137 lm/W  
Weight: 9.4 kg  
Scx: 0.05 m<sup>2</sup>



TLG\_CARA\_F\_L\_PostTop.jpg



TLG\_CARA\_M\_LMTP.wmf

This product contains light sources of energy efficiency class D.

**Carat**

**96634309 CT L 60L70-730 NR CL2 T60F ANT**

**THORN**