

## Beta 3

THORN

96634507 BETA 3 4100-830 HF LRO Q625

|                           |                  |      |  |    |  |  |  |        |                           |  |
|---------------------------|------------------|------|--|----|--|--|--|--------|---------------------------|--|
| IEC EN<br>60598-1<br>RG 0 | ↓ IP20<br>↑ IP44 | IK03 |  | CE |  |  |  | 650 °C | T <sub>a</sub> -20<br>+40 |  |
|---------------------------|------------------|------|--|----|--|--|--|--------|---------------------------|--|

### Beta 3


A square ceiling recessed LED luminaire. Fixed output LED driver. Class II electrical, IP44\_IP20, Impact strength: IK03. Body: sheet steel, white (close to RAL9016). Diffuser: Opalised PMMA with micro-prismatic foil inlay. Safety wire not included. Complete with 3000K LED.

UGR < 19 and L65 < 3000 cd/m<sup>2</sup> as per EN 12464

Dimensions: 622 x 622 x 34 mm  
Luminaire input power: 33.6 W  
Luminaire luminous flux: 3690 lm  
Luminaire efficacy: 110 lm/W  
Weight: 2.2 kg



TLG\_BET3\_F\_MREQ.jpg



TLG\_BET3\_M\_Q625.wmf

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at  $\pm 10\%$ . Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.  
© Thorn Lighting