

# IQ Beam

THORN

## 92927347 IQ BEAM 4300-840 MPT-F HFIX Q600

|                           |   |      |      |   |   |   |   |        |                           |  |
|---------------------------|---|------|------|---|---|---|---|--------|---------------------------|--|
| IEC EN<br>60598-1<br>RG 1 |  | IP20 | IK03 |  |  |  |  | 650 °C | T <sub>a</sub> -20<br>+40 |  |
|---------------------------|---|------|------|---|---|---|---|--------|---------------------------|--|

### IQ Beam

A linear optic, recessed modular LED luminaire for exposed T, plasterboard and concealed grid ceilings. DALI-2 dimmable, LED driver. Class I electrical, IP20, Impact strength: IK03. Body: white painted steel. Diffuser: micro prism structure acrylic with diffusing foil. Suitable for lay-in installation, pull up installation optional. Complete with 4000K LED.

Dimensions: 597 x 597 x 60 mm  
Luminaire input power: 32.2 W  
Luminaire luminous flux: 4300 lm  
Luminaire efficacy: 134 lm/W  
Weight: 4.26 kg



TLG\_IQBM\_F\_pers\_B.jpg



TLG\_IQBM\_M\_LDQ.wmf

This product contains a light source of energy efficiency class C.

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at  $\pm 10\%$ . Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.  
© Thorn Lighting