

IEC EN 60598-1 RG 1	UK CA	IP43	halogen	IK06	⏏	CE	⚡	EAC	⚡	850°C	T <sub>a</sub> -20 +25	
---------------------------	----------	------	---------	------	---	----	---	-----	---	-------	---------------------------	--


## Cetus

Surface mounted LED downlight. Fixed output LED driver.  
 Body: die-cast aluminium. Diffuser: polycarbonate, smooth reflector in white finish with wide beam. Trim: high quality, highly reflective polycarbonate. Class I electrical, IP43.  
 Installation plate to be fitted directly to ceiling, for mounting via BESA box or wire suspension use available accessory.  
 Electrical connection via 3/5 pole, push in, terminal block, Housing mounts to installation plate with twist and lock bayonet mechanism. Complete with 4000K LED

Dimensions: Ø181 x 182 mm  
 Luminaire input power: 7.7 W  
 Luminaire luminous flux: 1057 lm  
 Luminaire efficacy: 137 lm/W  
 Weight: 2.59 kg



TLG\_CTU3\_F\_MSF\_RWH.jpg



TLG\_CTU3\_M\_MSF.wmf

This product contains a light source of energy efficiency class C.

**Cetus**

**96634897 CETUS3 MSF 1000-840 EHF RWH**

**THORN**