

96634898 CETUS3 MSF 2000-840 EHF RWH

IEC EN 60598-1 RG 1	UK CA	IP43	halogen	IK06	⊕	CE	EAC	RoHS	REACH	850°C	T _a -20 +25
---------------------------	----------	------	---------	------	---	----	-----	------	-------	-------	---------------------------


Cetus

Surface mounted LED downlight. Fixed output LED driver.
 Body: die-cast aluminium. Diffuser: polycarbonate, smooth reflector in white finish with wide beam. Trim: high quality, highly reflective polycarbonate. Class I electrical, IP43.
 Installation plate to be fitted directly to ceiling, for mounting via BESA box or wire suspension use available accessory.
 Electrical connection via 3/5 pole, push in, terminal block, Housing mounts to installation plate with twist and lock bayonet mechanism. Complete with 4000K LED

Dimensions: Ø181 x 182 mm
 Luminaire input power: 15.3 W
 Luminaire luminous flux: 2048 lm
 Luminaire efficacy: 134 lm/W
 Weight: 2.59 kg



TLG_CTU3_F_MSF_RWH.jpg



TLG_CTU3_M_MSF.wmf

This product contains a light source of energy efficiency class C.

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Cetus

96634898 CETUS3 MSF 2000-840 EHF RWH

THORN