

Cetus

96635051 CETUS3 L LCS EHF RWH

IEC EN 60598-1 RG 1	UK CA			halogen	IK 06		CE				850°C	T <sub>a</sub> -20 +25	
---------------------------	----------	--	--	---------	-------	--	----	--	--	--	-------	---------------------------	--

Cetus


A low height, recessed LED downlight. Suitable for ceiling cut-outs Ø190-230 mm for easy refurbishments or fast initial installations. Remote, pluggable, Fixed output LED driver with DC functionality, adjustable 50-100%, NFC configurable. Loop in - loop out possible. Body: die-cast aluminium for thermal management. Diffuser: polycarbonate, smooth reflector in white finish with wide beam. Reflector and trim: high quality, highly reflective polycarbonate. Class II electrical, IP44 IP20. Spring clips suitable for ceiling thicknesses from 1 to 35 mm.

Equipped with LCS technology, with two lumen outputs (2000lm and 3400lm) and three colour temperatures (3000K, 3500K and 4000K) selectable from below by a rotary switch. Pre-set to 4000K, high luminous flux.

Dimensions: Ø248 x 100 mm  
Luminaire input power: 26.9 W  
Luminaire luminous flux: 3473 lm  
Luminaire efficacy: 129 lm/W  
Weight: 0.81 kg



TLG\_CTU3\_F\_L\_LED\_RWH\_Persp.jpg



TLG\_CTU3\_M\_EHFL.wmf

This product contains a light source of energy efficiency class D.