

# Beta 3

## 96635079 BETA 3 4800-830 HF E3 LRO Q625

IEC EN 60598-1 RG 0		IK03				650°C	T <sub>a</sub> 0 +25
---------------------------	--	------	--	--	--	-------	-------------------------

### Beta 3


A square ceiling recessed LED luminaire. Fixed output LED driver with 3 hour, manual test, emergency lighting circuit. Class I electrical, IP44\_IP20, Impact strength: IK03. Body: sheet steel, white (close to RAL9016). Diffuser: Opalised PMMA with micro-prismatic foil inlay. Safety wire not included. Complete with 3000K LED.

UGR < 19 and L65 < 3000 cd/m<sup>2</sup> as per EN 12464

Dimensions: 622 x 622 x 34 mm  
Luminaire input power: 39.2 W  
Luminaire luminous flux: 4320 lm  
Luminaire efficacy: 110 lm/W  
Weight: 3.8 kg



TLG\_BET3\_F\_MREQ.jpg



TLG\_BET3\_M\_Q625.wmf

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.