

Beta 3

THORN

96635079 BETA 3 4800-830 HF E3 LRO Q625

IEC EN 60598-1 RG 0			IK03				650°C		T _a 0 +25
---------------------------	---	---	------	---	---	---	-------	---	-------------------------

Beta 3


A square ceiling recessed LED luminaire. Fixed output LED driver with 3 hour, manual test, emergency lighting circuit. Class I electrical, IP44_IP20, Impact strength: IK03. Body: sheet steel, white (close to RAL9016). Diffuser: Opalised PMMA with micro-prismatic foil inlay. Safety wire not included. Complete with 3000K LED.

UGR < 19 and L65 < 3000 cd/m² as per EN 12464

Dimensions: 622 x 622 x 34 mm
Luminaire input power: 39.2 W
Luminaire luminous flux: 4320 lm
Luminaire efficacy: 110 lm/W
Weight: 3.8 kg



TLG_BET3_F_MREQ.jpg



TLG_BET3_M_Q625.wmf

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at $\pm 10\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting

Beta 3

96635079 BETA 3 4800-830 HF E3 LRO Q625

THORN