

96635142 CT S 12L35-730 NR CL1 T76F ANT

ISO 9223 C5	ELUG X 11 *	ida DAK SKY APPROVED	UK CA	11	IP66	IK08		CE						T _a 35
----------------	----------------	-------------------------	----------	----	------	------	--	----	--	--	--	--	--	-------------------

Carat


An elegant urban lantern with durable performance. Programmable LED driver, set for fixed output, driving 12 LEDs at 350mA. Body: small size, die-cast aluminium (EN AC-44300), powder coated textured anthracite (close to RAL7043). Shaft: anthracite (close to RAL7043). Cover: glass. Fixings: stainless steel with anti-galvanic treatment. Narrow Road optic, with Colour Rendering Index min.: 70 Correlated colour temperature*: 3000 Kelvin LEDs supplied. Class I electrical, Impact strength: IK08, IP66, T_a max.: 35°C. Supplied with Ø76mm spigot adaptor pre-fitted for post-top, 5° tilt.

Surge protection: 10kV single pulse common mode and 8kV multipulse common mode and 6kV multipulse differential mode. If permanent DALI system is connected, 6kV multipulse common and differential mode.

Dimensions: Ø435 x 81 mm
Luminaire input power: 14 W
Luminaire luminous flux: 1897 lm
Luminaire efficacy: 136 lm/W
Weight: 6.7 kg
Scx: 0.04 m²



TLG_CARA_F_S_PostTop.jpg



TLG_CARA_M_SMTP.wmf

This product contains a light source of energy efficiency class D.

Carat

96635142 CT S 12L35-730 NR CL1 T76F ANT

THORN